



**Tendering text: Ampatex Ombrello**  
**Weather protection, fully self-adhesive**

Item	Description of service
------	------------------------

1 General information

This weather protection also serves as an airtight layer and is bonded over the entire surface, is positioned on the warm side of the thermal insulation. All overlaps and connections must be airtight. Any damage to the area or unavoidable holes must be sealed. Technical details:

Roll size:	1.5 m x 50 m
s <sub>D</sub> value:	3.5 m
Weight:	130 g/m <sup>2</sup>
Fire index:	RF 3(cr), VKF
Fire behaviour:	E, EN 13501-1
Natural weathering period:	
Steep-pitched roof >10° and wall	3 months
Ceiling	1 month
CE marking:	EN13984:2013

2 Supply and install the weather protection on the existing flat furring, with overlaps at least 10 cm wide or along the overlap line. Ampatex Ombrello must be bonded airtight over the entire surface and without creases to a clean and dry surface. Seal any nail or screw heads on roof battens or similar <10° DN with Ampacoll BK 535 nail seal, for >10° DN with Ampacoll ND or nail sealing tapes Ampacoll ND.Band or Ampacoll ND duo.

Roof shape: .....

Roof pitch: .....

Quantity.....m<sup>2</sup>  
 Price per unit.....  
 Total price.....

3 Edgings / edge connections

3.1 Edgings / edge connections on chimneys, perimeter walls, etc. using Ampacoll Flexx Pro flexible adhesive tape.

Quantity.....m      Price per unit.....      Total price.....

4 Penetrations

4.1 Tape over penetration connections such as outlet vents, chimneys, etc. with Ampacoll BK 535 butyl rubber strip, 2 x 50 mm or 2 x 80 mm, for an airtight and rainproof seal.

Alternative use for straight/angular penetrations: Ampacoll Flexx Pro 150

Quantity.....units    Price per unit.....    Total price.....

4.2 Total edge length < 50 cm

Quantity.....units    Price per unit.....    Total price.....

4.3 Total edge length > 50 cm to 100 cm

Quantity.....units    Price per unit.....    Total price.....

4.4 Total edge length > 100 cm to 200 cm  
(penetrations with a total edge length of more than 200 cm are considered edgings / edge connections and are indicated there).

Quantity.....units    Price per unit.....    Total price.....

4.5 Roof windows or other flat penetrations using Ampacoll Flexx Pro flexible adhesive tape.

Alternative option:

Quantity.....m    Price per unit.....    Total price.....

5 Pre-treatment of unsuitable surfaces (supplementary to item 4)

5.1 For connections on porous, dusty or rough backings such as masonry, concrete, raw wood, etc., a primer coat of Ampacoll Primax or Airmax must be applied.

Quantity.....m    Price per unit.....    Total price.....

All product data and application tips can be found in the product inserts.

Further information and sources:

Ampack AG  
Seebleichstrasse 50  
CH-9401 Rorschach  
Tel. +41 71 858 38 00  
Fax +41 71 858 38 37  
E-mail: [ampack@ampack.ch](mailto:ampack@ampack.ch)  
[www.ampack.ch](http://www.ampack.ch)

## Note

### ***Considerations in terms of content***

Users will occasionally have to make changes to adapt to a specific situation. Similarly, suggestions for tendering texts can only cover standard situations. Custom solutions must be worked out for special circumstances. In its manufacturing process, Ampack AG places an emphasis on state-of-the-art technology and follows established practices in the construction industry as well as all applicable standards and statutory provisions. In the event of doubt, the details provided in the documentation or booklets/fliers published by Ampack AG are definitive.

### ***Legal considerations***

The drafting of tendering texts is a voluntary extra service provided free of charge by Ampack for the purposes of aiding architects, planners and fabricators. It is carried out to the best of our knowledge, but to the express exclusion of any liability arising from the provision of advice. See the General Terms and Conditions of Ampack AG for information in this regard.

### ***Authorisation for use by customers of Ampack AG***

The tendering texts are authorised for use by our customers (architects, planners and fabricators) for their own purposes. Sharing or publication of these texts in printed or electronic media is not permitted. Constructive comments and additions are welcomed by the author. In order to facilitate transcription to a tendering platform, unnecessary formatting has been avoided.

Ampack AG  
Marius Schorer  
Head of application technology  
Seebleichstrasse 50  
CH-9400 Rorschach  
Tel.: +41 (0) 71 858 38 00  
Fax.: +41 (0) 71 858 38 37  
[m.schorer@ampack.ch](mailto:m.schorer@ampack.ch)

Copyright Ampack AG, CH-9400 Rorschach  
19 August 2022